



Κωδικός	Φύλλα	Πάχος
71217	1,5 x 1,5 m	0,50mm
65605	1,5 X 1,5 m	0,80mm
71218	1,5 x 1,5 m	1,00mm
65608	1,5 X 1,5 m	1,50mm
65607	1,5 X 1,5 m	2,00mm
71219	1,5 x 1,5 m	2,50mm
66830	1,5 X 1,5 m	3,00mm
66831	1,5 x 1,5 m	4,00mm
71220	1,5 X 1,5 m	5,00mm

Διατίθενται σε φύλλα με πάχος απο 0,50mm έως 5,00mm

DESCRIPTION
 FLEXSEALS AF 240 is nitrile rubber based, asbestos-free sheet sealing material reinforced with synthetic and aramide fibres.

COLOUR
 Blue

SERVICES
 FLEXSEALS AF 240 is a gasket material with good chemical, mechanical and thermal properties. Suitable for general use.

MAXIMUM RECOMMENDED TEMPERATURE
 350°C (660°F)

MAXIMUM RECOMMENDED PRESSURE
 10 MPa (100 bar)

These temperature and pressure guides cannot necessarily be used simultaneously and may be apply at all thicknesses.

TYPICAL PHYSICAL PROPERTIES:

Thickness	0,75	1,50	mm
Density	1,79	1,84	g/cm ³
ASTM Compressibility	6.8	7.7	%
ASTM Recovery	≥50	≥50	%
ASTM Tensile Strength	≥12	≥12	MPa
BS Residual stress	≥29	≥22	MPa
DIN Gas Pearmeability	≤0.3	≤0.3	ml/min

AVAILABILITY:

Sheet size (m)	1,5x1,5m	1,5x1,00	1,5x3 m